



SPECIFICATIONS

FLEX STYLE GRASS DRILLS – END WHEEL DRIVE STYLE

	FLXII 86	FLXII 88	FLXII 812	FLXII 816	FLXII 818	FLXII 822
Number of Openers	6	8	12	16	18	22
Spacing of Openers (Precise measurement is 7-13/16")	8 in.	8 in.	8 in.	8 in.	8 in.	8 in.
Machine Width	7.0 ft.	8.3 ft.	11.0 ft.	13.7 ft.	15.0 ft.	17.7 ft.
Planting Width	4.0 ft.	5.3 ft.	8.0 ft.	10.7 ft.	12.0 ft.	14.7 ft.
Length (front to back, excluding tongue and cool season/grain box)	5.6 ft.	5.6 ft.	5.6 ft.	5.6 ft.	5.6 ft.	5.6 ft.
Length (front to back, including tongue)	11 ft.	11 ft.	11 ft.	11 ft.	11 ft.	11 ft.
Length (front to back, including tongue and cool season/grain box)	12 ft.	12 ft.	12 ft.	12 ft.	12 ft.	12 ft.
Machine Weight (standard drill, no options)	1,700 lbs.	2,000 lbs.	2,200 lbs.	3,000 lbs.	3,600 lbs.	4,800 lbs.
Machine Weight (including cool season box)	2,000 lbs.	2,440 lbs.	2,940 lbs.	3,965 lbs.	4,545 lbs.	5,430 lbs.
Machine Weight (including no-till option)	2,200 lbs.	3,000 lbs.	3,780 lbs.	5,085 lbs.	5,800 lbs.	6,970 lbs.
BOX CAPACITIES (Bu/Ft):						
Small Seed/Legume Box	0.25	0.25	0.25	0.25	0.25	0.25
Fluffy Seed Box	1.01	1.01	1.01	1.01	1.01	1.01
Cool Season/Grain Box	1.10	1.10	1.10	1.10	1.10	1.10
TRACTOR REQUIREMENTS:						
Standard Drill	25 h.p.	30 h.p.	40 h.p.	50 h.p.	60 h.p.	75 h.p.
Drill (including cool season/grain box)	25 h.p.	30 h.p.	40 h.p.	50 h.p.	60 h.p.	75 h.p.
No-Till, 3-Point Mount (requires tractor counterweights)	40 h.p.	60 h.p.	80 h.p.	100 h.p.	150 h.p.	175 h.p.
No-Till, Towed	30 h.p.	40 h.p.	50 h.p.	60 h.p.	75 h.p.	100 h.p.



SPECIFICATIONS

FLEX STYLE GRASS DRILLS – REAR WHEEL DRIVE STYLE

	FLXII 86RD	FLXII 88RD	FLXII 812RD	FLXII 816RD	FLXII 818RD	FLXII 822RD
Number of Openers	6	8	12	16	18	22
Spacing of Openers	8 in.	8 in.	8 in.	8 in.	8 in.	8 in.
Machine Width	5.0 ft.	6.3 ft.	9.0 ft.	11.7 ft.	13.0 ft.	15.7 ft.
Planting Width	4.0 ft.	5.3 ft.	8.0 ft.	10.7 ft.	12.0 ft.	14.7 ft.
Length (front to back, excluding tongue and cool season/grain box)	9.0 ft.	9.0 ft.	9.0 ft.	9.0 ft.	9.0 ft.	9.0 ft.
Length (front to back, including tongue)	15.0 ft.	15.0 ft.	15.0 ft.	15.0 ft.	15.0 ft.	15.0 ft.
Length (front to back, including tongue and cool season/grain box)	15.0 ft.	15.0 ft.	15.0 ft.	15.0 ft.	15.0 ft.	15.0 ft.
Machine Weight (standard drill, no options)	1,800 lbs.	2,100 lbs.	2,500 lbs.	3,100 lbs.	3,700 lbs.	4,900 lbs.
Machine Weight (including cool season box)	2,100 lbs.	2,540 lbs.	3,040 lbs.	4,065 lbs.	4,645 lbs.	5,530 lbs.
Machine Weight (including no-till option)	2,300 lbs.	3,100 lbs.	3,880 lbs.	5,185 lbs.	5,900 lbs.	7,070 lbs.
BOX CAPACITIES:						
Small Seed/Legume Box	0.25	0.25	0.25	0.25	0.25	0.25
Fluffy Seed Box	1.01	1.01	1.01	1.01	1.01	1.01
Cool Season/Grain Box	1.10	1.10	1.10	1.10	1.10	1.10
TRACTOR REQUIREMENTS:						
Standard Drill	25 h.p.	30 h.p.	40 h.p.	50 h.p.	60 h.p.	75 h.p.
Drill (including cool season/grain box)	25 h.p.	30 h.p.	40 h.p.	50 h.p.	60 h.p.	75 h.p.
No-Till, 3-Point Mount (requires tractor counterweights)	40 h.p.	60 h.p.	80 h.p.	100 h.p.	150 h.p.	175 h.p.
No-Till, Towed	30 h.p.	40 h.p.	50 h.p.	60 h.p.	75 h.p.	100 h.p.



SPECIFICATIONS

FLEX STYLE GRAIN DRILLS – END WHEEL DRIVE

	FLXII 88G	FLXII 812G	FLXII 816G	FLXII 818G	FLXII 822G
Number of Openers	8	12	16	18	22
Spacing of Openers	8 in.	8 in.	8 in.	8 in.	8 in.
Machine Width	8.5 ft.	11 ft.	13.5 ft.	15 ft.	18 ft.
Planting Width	5.3 ft.	8 ft.	10.7 ft.	12 ft.	15 ft.
Length (front to back, excluding tongue)	5.7 ft.	5.7 ft.	5.7 ft.	5.7 ft.	5.7 ft.
Length (front to back, including tongue)	11.7 ft.	11.7 ft.	11.7 ft.	11.7 ft.	11.7 ft.
Machine Weight (standard drill, no options)	1,500 lbs.	2,000 lbs.	2,500 lbs.	3,000 lbs.	3500 lbs.
Machine Weight (including no-till option)	2,060 lbs.	2,840 lbs.	3,620 lbs.	4,260 lbs.	5040 lbs.
BOX CAPACITIES (Bu/Ft):					
Small Seed/Legume Box	0.25	0.25	0.25	0.25	0.25
Grain Box	2.00	2.00	2.00	2.00	2.00
TRACTOR REQUIREMENTS:					
Standard Drill	30 h.p.	40 h.p.	50 h.p.	60 h.p.	75 h.p.
No-Till, 3-Point Mount (requires tractor counterweights)	60 h.p.	80 h.p.	100 h.p.	150 h.p.	200 h.p.
No-Till, Towed	40 h.p.	50 h.p.	60 h.p.	75 h.p.	100 h.p.